



## Welded Master Link X-002

### Product information

Welded Master Link designed for 1-2 legs Wire Rope and Chain Slings. The engineered flat makes it simple to insert wire rope thimbles on our links. Suitable for omega links.

At least 25% greater WLL than traditional Grade 8 products.

Proof Load tested at 2.5 times the WLL with certification for each batch manufactured. Tempering temperature at a minimum of 400°C.

**Material:** Quenched and Tempered Alloy Steel.

**Marking:** According to standard, CE-marked, Type, manufacturer ID, traceability.

**Temperature range:** -40° up to +200°C (without reduction in WLL).

**Finish:** Blue painted.

**Standard:** EN 1677-4

AS 3776

**Safety factor:** 4:1

**Grade:** 10

Part Code	Code	WLL ton	EWL mm	For chain gr 10 Ø 2 leg mm	For chain gr 10 Ø 1 leg mm	A mm	B mm	D mm	Weight (kg)
402100280420	BD-13	2.8	110	6	7,8	110	60	13	0.3
402100400420	BD-16	4	110	7,8	10	110	60	16	0.5
402100670420	BD-19	6.7	135	10	13	135	75	19	0.9
402100850420	BD-22	8.5	160	10	13	160	90	22	1.5
402101150420	BD-28	11.5	180	13	16	180	100	28	2.7
402101700420	BD-32	17	200	16	20	200	110	32	3.9
402102510420	BD-36	25.1	260	20	22	260	140	36	6.3
402103830420	BD-45	38.3	300	22	26	300	180	45	11.8
402104500420	BD-50	45	300	32	28	300	200	50	15.2

## Blueprint

