

## Modular Spreader Beam – MOD 6



### Product information

#### The standard range

Modular spreader beams provide the ideal solution for most lifting requirements – versatile and cost-effective. Modulift MOD 6 is available with capacity up to 6 t at 3.6 m and up to 4.5 m at a lower capacity.

[Click here to see the load v span chart for the standard range](#)

The modular configuration and interchangeable components enable Modulift spreaders to be reused over many lifts. Designed by Modulifts engineering experts and manufactured in their own specialist facilities; the Modulift range are the leading modular spreader beams on the market.

#### How the spreader beam is configured

Every Modulift modular spreader beam consists of a pair of end units and a pair of drop links, with interchangeable struts that can be bolted into the assembly between the end units to either lengthen or shorten the beam to suit the requirements of the lift, making them reusable at different spans. The different components are shown in the table below. If you need help to configure your spreader beam, please contact us.

**Australian Standard:** AS 4991

Part Code	Type	Weight (kg)
62080006DL003	Drop Link WLL 3t	0.6
62080006010	100 mm Strut	2
62080006020	200 mm Strut	2.7
62080006EU003	End Unit WLL 3t	3
62080006030	300 mm Strut	3.4
62080006060	600 mm Strut	5.4
62080006100	1000 mm Strut	8.1
6208CMOD06	Set of 4 corners	-
62080006BOLTE	Set of bolts, nuts and washers	-

## Blueprint

