



Eye Sling Hook X-044/S

Product information

- At least 25% greater WLL than traditional Grade 8 products.
- Proof Load tested at 2,5 times the WLL with certification for each batch manufactured.
- Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Magnaflux crack detection is performed 100% on each batch.

Material: Quenched and Tempered Alloy Steel

Marking: According to standard, Size, grade, manufacturer ID, traceability.

Temperature range: -40°C up to +200°C (without reduction in WLL).

Finish: Blue painted.

Standard: EN 1677-2

Safety factor: 4:1

Grade: 10

Australian Standard: AS 3776

Part Code	Chain size mm	WLL ton	A mm	D mm	H mm	K mm	P1 mm	T mm	Weight (kg)
4023001400010	6	1.4	20	10	19	80	23	17	0.3
4023002500010	7-8	2.5	25	12	22	98	28	20	0.5
4023004000010	10	4	33	15	30	122	36	23	1
4023006700010	13	6.7	40	18	38	152	40	28	1.8
4023010000010	16	10	51	22	44	185	44	36	3.4
4023016000010	20	16	61	27	64	230	54	48	7.3
4023019000010	22	19	51	31	61	245	76	52	9.3
4023026500010	26	26.5	65	34	77	285	77	61	13.5
4023040000010	32	40	91	41	79	358	114	65	22

Blueprint

