



Lifting Eye Starpoint RUD VRS-F

Product information

Star shaped design, can be adjusted to the direction of pull. Higher load capacities than DIN 580-Eyebolts

Material: Forged high tensile engineering steel, crack detekted.

Marking: According to standard, WLL

Finish: Striking fluorescent pink powder coating

Standard: EN 1677-1

Australian Standard: AS 3776

Safety factor: 4:1

Part Code	Code	WLL ton	Thread	Thread	B mm	C mm	D mm	E mm	G mm	I mm	K mm	L mm	N mm	T mm	Weight (kg)
421100030260	VRS-F	0.3	M8	M8	11	9	25	25	30	16.3	47	12	6	35	0.12
421100040260	VRS-F	0.4	M10	M10	11	9	25	25	30	16.3	47	15	6	35	0.12
421100080260	VRS-F	0.75	M12	M12	13	10	30	30	34	19.8	56	18	8	42	0.21
421100230260	VRS-F	2.3	M20	M20	17	16	40	41	50	-	76	30	12	58	0.6
421100320260	VRS-F	3.2	M24	M24	20	19	49	51	60	35	92	36	14	70	1.05
421100450260	VRS-F	4.5	M30	M30	26	24	60	66	75	44	114	45	17	87	2.08
421100700260	VRS-F	7	M36	M36	32	29	73	76	98	53	135	54	22	104	3.49
421100900260	VRS-F	9	M42	M42	37	33	84	86	111	62	158	63	24	121	5.4
421101200260	VRS-F	12	M48	M48	42	42	94	100	128	70	180	72	27	138	8.17

Blueprint

