



Grab Hook Pewag PW

Product information

Thanks to the special design of the chain contact area, this standard shortening hook ensures optimal interaction between chain and hook. Even when shortened, the load capacity is not reduced.

Material: High duty grade 10.

Marking: According to standard, CE-marked, Pewag or PW, winner or 10, H16, batch code and type.

Temperature range: -40°C up to +380°C.

Finish: Orange powder coated.

Standard: EN 1677-1

Australian Standard: AS 3776

Safety factor: 4:1

Grade: 10

Australian Standard: AS 3776

Part Code	Code	WLL ton	EWL	b mm	d1 mm	d2 mm	e mm	g mm	Weight (kg)
402300100520	PW 5	1	47	40	11	9	47	7	0.13
402300140520	PW 6	1.4	50	44	12	9	50	7	0.15
402300250520	PW 7/8	2.5	65	57	16	12	65	9	0.37
402300400520	PW 10	4	77	77	20	14	77	12	0.7
402300670520	PW 13	6.7	101	92	26	19	101	15	1.56
402301000520	PW 16	10	121	113	32	23	121	19	2.9
402301600520	PW 19/20	16	151	150	36	27	151	25	6.15
402301900520	PW 22	19	170	165	42	31	170	27	8.3
402302650520	PW 26	26.5	201	195	50	37	201	32	13.8
402304000520	PW 32	40	243	242	60	43	243	38	25

Blueprint

