



Steel Wire Rope 6x7-WSC

Product information



Rope construction: 6x7-WSC (7x7)

Marking: According to standard

Temperature range: -40°C up to +200°C, for operating temperatures between 100 °C and 200 °C reduce MBF by minus 10 %

Standard: EN 12385-4

AS 3569

Fill factor: 0,55

Australian Standard: AS 3569

Stay rope



Agriculture and livestock



General use



Part Code	Rope diameter mm	Tensile strength N/mm ²	Steel area mm ²	Min. breaking force kN	Finish	Weight kg/100m
101100104250160	1	1,770	-	-	Galvanized	-
101100154250160	1.5	1,770	-	-	Galvanized	-
101100184450160	1.8	1,770	-	-	Heavy galvanized	-
101100204450160	2	1,770	-	-	Heavy galvanized	-
101100234450160	2.3	1,770	-	-	Heavy galvanized	-
101100304250160	3	1,770	-	-	Galvanized	-
101100404450160	4	1,770	-	-	Heavy galvanized	-
101100504250160	5	1,770	-	-	Galvanized	-
101100604250160	6	1,770	-	-	Galvanized	-
101100704250160	7	1,770	-	-	Galvanized	-
101100804250160	8	1,770	-	-	Galvanized	-
101100904450160	9	1,770	-	-	Heavy galvanized	-
101101004450160	10	1,770	-	-	Heavy galvanized	-
101101104250160	11	1,770	-	-	Galvanized	-
101101204450160	12	1,770	-	-	Heavy galvanized	-
101101304250160	13	1,770	-	-	Galvanized	-
101101404250160	14	1,770	-	-	Galvanized	-
101101504250160	15	1,770	-	-	Galvanized	-
101101604250160	16	1,770	-	-	Galvanized	-
101101804250160	18	1,770	-	-	Galvanized	-
101102004250160	20	1,770	-	-	Galvanized	-