

Roundsling Supra Plus/Magnum

Product information



Design: Load carrying yarn covered with “seamless” color coded protection sleeve. Supra Plus and Magnum have an extra strong protection sleeve. As well as a blue label the Supra plus is provided with a RFID chip for identification.

Stretch with working load: 2-3%.

Length tolerance: Nominal length (EWL) $\pm 2\%$.

Material: Polyester. Resistant to most acids but not strong alkalizes.

Marking: According to standard, The slings are provided provided with a RFID chip for identification and a blue label with manufacturer's symbol, working load limit (WLL), length, CE marking and a label with handling instr

Temperature range: app. -40° - $+100^{\circ}\text{C}$.

Standard: EN 1492-2

AS 4497

Safety factor: 7:1.

| Part Code | WLL ton |
|------------------|--------------------|
| 34010010XXX0180 | 1 |
| 34010020XXX0180 | 2 |
| 34010030XXX0180 | 3 |
| 34010040XXX0180 | 4 |
| 34010050XXX0180 | 5 |
| 34010060XXX0180 | 6 |
| 34010080XXX0180 | 8 |
| 34010100XXX0180 | 10 |
| 34010150XXX0180 | 15 |
| 34010200XXX0180 | 20 |
| 34010250XXX0180 | 25 |
| 34010300XXX0180 | 30 |
| 34010400XXX0180 | 40 |
| 34010500XXX0180 | 50 |
| 34010600XXX0180 | 60 |
| 34010800XXX0180 | 80 |
| 34011000XXX0180 | 100 |

Blueprint

