



Endurance 50DB

Product information



Excellent Resistance to Rotation giving over three times more lifting height than a conventional 18 x 7 class rope
Flexibility is optimised by the unique strand and rope construction.
Langs Lay construction combines excellent wear characteristics with efficient spooling on the drum.

Standard: EN 12385-4

ISO 4309 Rope Category No: All Diameters **RCN.23-1**

Features: Very High Breaking Load

Material: High Carbon Steel

Marking: On Termination ID and CE mark

Finish: Galvanised as standard

Fill factor: 0.64

RCN: 23-1

Australian Standard: AS 3569

Part Code	Rope diameter mm	Tensile strength N/mm²	Min. breaking force kN	Finish	Weight kg/100m
102100806270139	8	1,960	-	Galvanized	-
102100906270139	9	1,960	-	Galvanized	-
102101006270139	10	1,960	-	Galvanized	-
102101106270139	11	1,960	-	Galvanized	-
102101206270139	12	1,960	-	Galvanized	-
102101306270139	13	1,960	-	Galvanized	-
102101406270139	14	1,960	-	Galvanized	-
102101506270139	15	1,960	-	Galvanized	-
102101606270139	16	1,960	-	Galvanized	-
102101706270139	17	1,960	-	Galvanized	-
102101806270139	18	1,960	-	Galvanized	-
102101906270139	19	1,960	-	Galvanized	-
102102006270139	20	1,960	-	Galvanized	-
102102106270139	21	1,960	-	Galvanized	-
102102206270139	22	1,960	-	Galvanized	-