



Endurance 50DB

Product information



Excellent Resistance to Rotation giving over three times more lifting height than a conventional 18 x 7 class rope
Flexibility is optimised by the unique strand and rope construction.
Langs Lay construction combines excellent wear characteristics with efficient spooling on the drum.

Standard: EN 12385-4

ISO 4309 Rope Category No: All Diameters **RCN.23-1**

Features: Very High Breaking Load

Material: High Carbon Steel

Marking: On Termination ID and CE mark

Finish: Galvanised as standard

Fill factor: 0.64

RCN: 23-1

Australian Standard: AS 3569

Part Code	Rope diameter mm	Min. breaking force kN 1960 N/mm²	Finish	Weight kg/100m
102100806270139	8	49.6	Galvanized	27.6
102100906270139	9	62.8	Galvanized	34.4
102101006270139	10	77.6	Galvanized	42.5
102101106270139	11	93.9	Galvanized	51.8
102101206270139	12	112	Galvanized	61.9
102101306270139	13	131	Galvanized	72.8
102101406270139	14	152	Galvanized	83.6
102101506270139	15	175	Galvanized	96
102101606270139	16	199	Galvanized	110
102101706270139	17	224	Galvanized	121
102101806270139	18	251	Galvanized	136
102101906270139	19	280	Galvanized	156
102102006270139	20	310	Galvanized	168
102102106270139	21	342	Galvanized	185
102102206270139	22	375	Galvanized	206