

Electric Winch Pacific

Product information



Comeup Electric Winches come in various sizes and lifting capacities. All winches are precision engineered and constructed from heavy duty material which creates a high performance product with low maintenance; suited for a wide range of applications. The electric winches feature the CP, CWG and CWL range.

Features:

- Lightweight and compact design for easy installation and portable use.
- Electromagnetic spring-applied failsafe brake designed for both static and dynamic loading which applies automatically in the event of power loss.
- IP65 pendant control.
- 24V x 3 meter push button control supplied as standard with all CP and CWG models.
- Compact load sharing design of the heat-treated planetary gear which ensures quiet operation and long life.
- Emergency stop function switch is featured on all models.
- Optional cordless radio remote control available on request.

WLL (kg)	Lifting height m	Model	Operation voltage (V)	Wire rope dia x m	A mm	B mm	C mm	D mm	E mm	F mm	Weight (kg)
200	45	CWL	240 x 1	5 x 46	8 - Ø11	152	135	415.5	210	270	30
200	29	CP	240 x 1	6 x 30	6 - Ø10.5	142	142	510	210	241	32
200	69	CWL	240 x 1	5 x 71	8 - Ø11	207	135	470.5	210	270	33
250	29	CP	240 x 1	6 x 30	6 - Ø10.5	142	142	548	210	241	34
300	29	CWG	415 x 3	6 x 30	6 - Ø10.5	142	142	477	210	241	32
300	29	CP	240 x 1	6 x 30	6 - Ø10.5	142	142	576	210	241	38
300	58	CWL	240 x 1	6 x 60	8 - Ø11	207	135	556	210	270	40
300	58	CWG	240 x 1	6 x 60	4 - Ø13.5	197	156	624	252	300	42
400	58	CWG	415 x 1	9 x 60	4 - Ø16	400	325	937	367	425	120
500	58	CP	415 x 3	7 x 60	4 x Ø13.5	267	156	704	260	299	54
500	58	CP	240 x 1	7 x 60	4 x Ø13.5	267	156	694	260	299	55
500	58	CWG	415 x 3	9 x 60	4 - Ø16	400	325	922	367	425	120
500	127	CWG	415 x 3	8 x 130	6 - Ø16	460	300	1,002	247	360	-
650	58	CWG	415 x 3	9 x 60	4 - Ø16	400	325	940	367	425	154
750	58	CP	415 x 3	9 x 60	6 - Ø16	400	300	870	347	360	135
900	58	CWG	415 x 3	10 x 60	4 - Ø19	500	370	974	400	445	185
1,100	97	CWG	415 x 3	12 x 100	4 - Ø19	620	425	1,120	470	520	250
2,200	97	CWG	415 x 3	16 x 100	4 - Ø22	600	499	1,246	565	658	400
3,500	144	CWG	415 x 3	18 x 150	8 - Ø30	847	680	1,439	740	860	800
5,000	192	CWG	415 x 3	22.4 x 200	8 - Ø32	920	680	1,860	740	905	1,380

Blueprint

