



## Chain Block VL5 OLL Vital

### Product information

Built on the standard model, with ball-bearing in the loading hook. This block has a built-in overload protection. Delivered with either a black (NB) or zinc plated (ZP) chain, but for use offshore, the ZP-model is recommended.

**Material:** Steel

**Marking:** According to standard, CE-marked, WLL, serial number

**Temperature range:** -10°C til +50°C

**Standard:** EN 13157, EN 818-7

**Safety factor:** 4:1

<b>Part Code</b>	<b>WLL ton</b>	<b>Lifting height m</b>	<b>a mm</b>	<b>b mm</b>	<b>c mm</b>	<b>g mm</b>	<b>Weight (kg)</b>
500100050300200	0.5	3	129	145	285	27	8.3
500100051000204	0.5	10	129	145	285	27	8.3
500100100300200	1	3	149	158	315	30	11.3
500100100600204	1	6	149	158	315	30	11.3
500100150300200	1.5	3	149	177	340	34	13.5
500100150600204	1.5	6	149	177	340	34	13.5
500100200300200	2	3	181	204	380	37	21
500100200500204	2	5	181	204	380	37	21
500100200800205	2	8	181	204	380	37	21
500100300300200	3	3	149	208	475	43	22
500100500300200	5	3	181	263	600	47	40
500100750350200	7.5	3.5	181	354	700	67	59

# Blueprint

