

## Lifting Eye RUD ACP-TURNADO

### Product information



- Unique RUD spring mechanism
- No stopping of the lifting bale
- No dangerous transverse loads - no worst case
- Integrated RFID transponder to make checks easier
- Wear lenses for checking discard criteria

According to the EC-Machinery Directive 2006/42/EC

**Marking:** According to standard

**Temperature range:** -40°C up to +100°C.

**Standard:** EN ISO 12100

**Standard:** EN 1677-1










*Australian Standard: AS 3776*

**Safety factor:** 4:1



Part Code	WLL ton	Thread	A mm	B mm	C mm	D mm	E mm	F mm	G mm	H mm	I mm	K mm	L mm	M mm	N mm	T mm	Weight (kg)
42157912061	0.7	M8	-	11	10.5	38	30	12	28	45	13	58	40	M8	5	83	0.36
42157909316	2.5	M16	-	14	14	50	40	22	36	68	24	76	58	M16	10	107	0.88
42157909317	4	M20	-	17	17.25	50	45	26.5	43.5	82.5	30	89	70	M20	12	118	1.41
42157909318	6.3	M24	-	23	23	66	60	34	55	104	36	120.5	89	M24	14	154	3.16
42157909319	8	M30	-	29	27	75	75	41.5	68.5	128.7	46	148	110	M30	17	183	5.69
42157911052	12.5	M36	106	32	32	82	70	45	60	128	55	168	105	M36	22	189	7.1
42157911053	16	M42	106	32	32	82	70	53	60	136	65	168	113	M42	24	189	7.5
42157912630	20	M48	127	45	45	103	90	61	78.5	169	75	204	139	M48	24	235	16.04
42157912631	24	M52	123.5	45	45	103	95	65	108	173	75	204	145	M52	24	232	16.34
42157912632	27	M56	123.5	45	45	103	95	70	108	178	75	204	150	M56	24	232	16.5
42157912633	32.5	M64	123.5	45	45	103	95	80	108	188	75	204	-	M64	24	232	17.19

## Technical data

Lifting method											
Number of legs	1	1	2	2	2	2	2	3 / 4	3 / 4	3 / 4	
Inclination angle <math>\beta</math>	0°-7°	90°	0°-7°	90°	0-45°	>45-60°	Un-symm.	0-45°	>45-60°	Unsymm.	
Factor	1	1	2	2	1.4	1	1	2.1	1.5	1	
<b>factor 4:1</b>	<b>Safety factor 4:1</b>	<b>For max. total load in metric tons, bolted and adjusted to the direction of pull</b>									
	ACP M8	0.7	0.7	1.4	1.4	0.98	0.7	0.7	1.47	1.05	0.7
	ACP M10	1	1	2	2	1.4	1	1	2.1	1.5	1
	ACP M12 / 1/2"	1.35	1.35	2.7	2.7	1.9	1.35	1.35	2.84	2	1.35
	ACP M16 / 5/8"	2.5	2.5	5	5	3.5	2.5	2.5	5.25	3.75	2.5
	ACP M20 / 3/4"	4	4	8	8	5.6	4	4	8.4	6	4
	ACP M24 / 1"	6.3	6.3	12.6	12.6	8.8	6.3	6.3	13.2	9.4	6.3
	ACP M30 / 1 1/4"	8	8	16	16	11.2	8	8	17	11.8	8
	ACP M36	15	12.5	30	25	17	12.5	12.5	26.5	19	12.5
	ACP 1 1/2"	16	14	32	28	19.6	14	14	29.4	21	14
	ACP M42	18	16	36	32	22.4	16	16	33.6	24	16
	ACP 1 3/4"	18	16	36	32	22.4	16	16	33.6	24	16
	ACP M48	25	20	50	40	28	20	20	42	30	20
	ACP 2"	25	22	50	44	30.8	22	22	46.2	33	22
	ACP M52	26	24	52	48	33.6	24	24	50.4	36	24
ACP M56	32.5	27	65	54	38	27	27	57	40.5	27	
ACP M64 / M72 / M80 M90 / M100	35	32.5	70	65	46	32.5	32.5	69	49	32.5	

# Blueprint

