

Round Sling EXTREEMA® XS



Product information

The extra thin, light weight EXTREEMA® XS round slings WLL 3T, WLL 5T & WLL 10T make it possible to lift heavy payloads, when you have to work with limited spaces.

With an extremely small diameter and a D:d ratio of 1:1 (recommended 1:1,5 for longer life cycle), it also enables you to work with regular classic model bow shackles instead of more expensive wide body or sling shackles. It is possible to equip the sling with different kinds of optional protections. The slings are available in effective working lengths in the range of 0.3m up to 20 m. Shown variants are standard lengths but other lengths in this range are possible on request.

By making use of the WLL 3T (6T basket), WLL 5T (10T basket) and WLL 10T (20T basket) EXTREEMA® slings, you can replace all polyester slings from 1T up to 20T. This saves you costs in storage, logistics, purchasing and disposal, while supplying you or your employees with a more efficient, more environmentally friendly and faster workflow.

Features and benefits

- Saving costs
- D:d ratio of 1:1
- Environmentally friendly
- Light in weight
- Flexible
- Less storage
- Long life cycle
- Access to limited lifting space
- Safer lifting operations
- Improving workflow

Material: HMPE -Dyneema®

Marking: According to standard, CE-marked

Temperature range: -50°C up to +70°C

Standard: EN 1492-2
except material

Safety factor: 7:1

Part Code	WLL ton
340500300050030	3
340500300080030	3
340500300100030	3
340500300150030	3
340500300200030	3
340500300250030	3
340500300300030	3
340500300400030	3
340500300500030	3
340500300600030	3
340500500050030	5
340500500100030	5
340500500150030	5
340500500200030	5
340500500250030	5
340500500300030	5
340500500400030	5
340500500500030	5
340500500600030	5
340501000150030	10
340501000200030	10
340501000300030	10

340501000400030

10

340501000500030

10

340501000600030

10

340501000050030

10

Technical data